

**SECTION 1. Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Product code : Hygienfresh Pavimenti/Superfici Note di Pulito

Trades code : A85-025

Product line: Hygienfresh

UFI: 7M12-00AS-Q00A-UDDQ

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

Gel detergent for floors with Microcapsules-slow release fragrance

Sectors of use:

Industrial Manufacturing[SU3], Private households (= general public = consumers)[SU21], Public domain (administration, education, entertainment, services, craftsmen)[SU22]

Uses advised against

Do not use for purposes other than those listed

**1.3. Details of the supplier of the safety data sheet**

Tintolav s.r.l. - Via M. D' Antona 7 - 10028 Trofarello (TO) Tel. 011/649.68.27 Fax 011/649.67.42

Email: info@tintolav.com - Sito internet: www.tintolav.com

Email tecnico competente: a.conedera@tintolav.com

National contact: Malta: Emergency Ambulance 112

Accident &amp; Emergency Department 2545 4030

**1.4. Emergency telephone number**

The UK National Poisons Emergency number +44 (0)870 600 6266

London: Emergency 24 hour telephone +44 (0) 207188 0100

**SECTION 2. Hazards identification****2.1. Classification of the substance or mixture**

2.1.1 Classification according to Regulation (EC) No 1272/2008:

Pictograms:

GHS07

Hazard Class and Category Code(s):

Eye Irrit. 2

Hazard statement Code(s):

H319 - Causes serious eye irritation.

If brought into contact with eyes, the product, causes significant irritations which may last for more than 24 hours.

**2.2. Label elements**

Labelling according to Regulation (EC) No 1272/2008:

Pictogram, Signal Word Code(s):

GHS07 - Warning



**Hazard statement Code(s):**

H319 - Causes serious eye irritation.

**Supplemental Hazard statement Code(s):**EUH208 - Contains  $\alpha$ -Hexylcinnamaldehyde, reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1), Isoeugenol. May produce an allergic reaction.**Precautionary statements:****General**

P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children.

**Prevention**

P264 - Wash your hand thoroughly after handling.

**Response**

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313 - If eye irritation persists: Get medical advice/attention.

**Contains (Reg.CE 648/2004):**

&lt; 5% Anionic surfactants, Non-ionic surfactants, Perfumes, EDTA and salts, Hexyl cinnamal, Citronellol, Geraniol, Eugenol, Alpha isomethyl ionone, Limonene, Coumarin, methylchloroisothiazolinone, methylisothiazolinone.

Content of VOC ready to use condition: 5,11 %

UFI: 7M12-00AS-Q00A-UDDQ

**2.3. Other hazards**

Based on the available data, no PBT or vPvB substances are present in accordance with Regulation (EC) 1907/2006, annex XIII

Based on available data, there are no substances that interfere with the Endocrine System in accordance with Regulation (EU) 2017/2100

No information on other hazards

**SECTION 3. Composition/information on ingredients****3.1 Substances**

Irrelevant

**3.2 Mixtures**

Refer to paragraph 16 for full text of hazard statements

Note B - Some substances (acids, bases, etc.) are placed on the market in aqueous solutions at various concentrations and, therefore, these solutions require different classification and labelling since the hazards vary at different concentrations. In Part 3 entries with Note B have a general designation of the following type: 'nitric acid ... %'. In this case the supplier must state the percentage concentration of the solution on the label. Unless otherwise stated, it is assumed that the percentage concentration is calculated on a weight/weight basis.

Substance	Concentration[w/w]	Classification	Index	CAS	EINECS	REACH
Propan-2-ol - FEMA 2929	$\geq 1 < 5\%$	Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336 ATE oral = 2.100,0 mg/kg ATE dermal = 2.100,0 mg/kg ATE inhal = 29,0mg/l/4 h	603-117-00-0	67-63-0	200-661-7	ND
Alcohols, C13-15, branched and linear, ethoxylated	$\geq 1 < 5\%$	Acute Tox. 4, H302; Eye Dam. 1, H318; Aquatic Chronic 3, H412 Limits: Eye Irrit. 2, H319 $3 \leq \%C < 10$ ; Eye Dam. 1, H318 $\%C > 10$ ; 1 1 ATE oral $> 300,0$ mg/kg	ND	157627-86-6	ND	ND
Sodium Lauryl Ether sulfate	$\geq 1 < 5\%$	Skin Irrit. 2, H315; Eye Dam. 1, H318; Aquatic Chronic 3, H412 Limits: Eye Dam. 1, H318 $\%C \geq 10$ ; Eye Irrit. 2, H319 $5 \leq \%C < 10$ ; 1 1 ATE oral = 2.000,0 mg/kg ATE dermal = 2.000,0 mg/kg ATE inhal = 4.100,0mg/l/4 h	ND	68891-38-3	500-234-8	01-2119488 639-16
ethanol	$\geq 0,1 < 1\%$	Flam. Liq. 2, H225 ATE oral = 7.060,0 mg/kg ATE dermal = 20.000,0 mg/kg ATE inhal = 20.000,0mg/l/4 h	603-002-00-5	64-17-5	200-578-6	01-2119457 610-43
$\alpha$ -Hexylcinnamaldehyde	$\geq 0,1 < 1,00\%$	Skin Sens. 1, H317; Aquatic Chronic 2, H411 ATE oral = 2.450,0 mg/kg	ND	101-86-0	202-983-3	01-2119533 092-50
Isoeugenol	$< 0,1\%$	Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1A, H317; Eye Irrit. 2, H319 Limits: Skin Sens. 1A, H317 $\%C \geq 0,01$ ;	604-094-00-X	97-54-1	202-590-7	ND
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1) Note: B	$< 0,1\%$	EUH071; Acute Tox. 3, H301; Acute Tox. 2, H310; Skin Corr. 1C, H314; Skin Sens. 1, H317; Eye Dam. 1, H318; Acute Tox. 2,	613-167-00-5	55965-84-9	ND	ND

Substance	Concentration[w/w]	Classification	Index	CAS	EINECS	REACH
		H330; Aquatic Acute 1, H400; Aquatic Chronic 1, H410 Limits: Skin Corr. 1C, H314 %C >=0,6; Skin Irrit. 2, H315 0,06<=%C <0,6; Eye Dam. 1, H318 %C >=0,6; Eye Irrit. 2, H319 0,06<=%C <0,6; Skin Sens. 1A, H317 %C >=0,0015; 100 100				
1,2-benzisothiazol-3(2H)-one	< 0,1%	Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317; Eye Dam. 1, H318; Aquatic Acute 1, H400 Limits: Skin Sens. 1, H317 %C >=0,05; , EUH208 0,005<=%C <0,05; 1 ATE oral = 1.020,0 mg/kg	613-088-00-6	2634-33-5	220-120-9	ND

## SECTION 4. First aid measures

### 4.1. Description of first aid measures

#### Inhalation:

Air the area. Move immediately the contaminated patient from the area and keep him at rest in a well ventilated area. If you feel unwell seek medical advice.

#### Direct contact with skin (of the pure product):

Take contaminated clothing Immediately off.

Wash immediately with plenty of running water and possibly with soap, the areas of the body that have, or are only suspected to have, come in contact with the product.

In case of contact with skin, wash immediately with water and soap.

#### Direct contact with eyes (of the pure product):

Wash immediately and thoroughly with running water, keeping eyelids open for at least 10 minutes, then protect your eyes with a dry sterile gauze. Seek medical advice immediately

#### Ingestion:

Not hazardous. It's possible to give activated charcoal in water or liquid paraffin medicine

### 4.2. Most important symptoms and effects, both acute and delayed

No data available.

### 4.3. Indication of any immediate medical attention and special treatment needed

If eye irritation persists: Get medical advice/attention.

If medical advice is needed, have product container or label at hand.

## **SECTION 5. Firefighting measures**

### **5.1. Extinguishing media**

Advised extinguishing agents:

Water spray, CO<sub>2</sub>, foam, dry chemical, depending on the materials involved in the fire.

Extinguishing means to avoid:

Water jets. Use water jets only to cool the surfaces of the containers exposed to fire.

### **5.2. Special hazards arising from the substance or mixture**

No data available.

### **5.3. Advice for firefighters**

Use protection for the breathing apparatus

Safety helmet and full protective suit.

The spray water can be used to protect the people involved in the extinction

You may also use selfrespirator, especially when working in confined and poorly ventilated area and if you use halogenated extinguishers (Halon 1211 fluobrene, Solkan 123, NAF, etc...)

Keep containers cool with water spray

## **SECTION 6. Accidental release measures**

### **6.1. Personal precautions, protective equipment and emergency procedures**

6.1.1 For non-emergency personnel:

Leave the area surrounding the spill or release. Do not smoke

Wear gloves and protective clothing

6.1.2 For emergency responders:

Wear gloves and protective clothing Suitable: LaTeX, nitrile, PVC

Eliminate all unguarded flames and possible sources of ignition. No smoking.

Provision of sufficient ventilation.

Evacuate the danger area and, in case, consult an expert.

### **6.2. Environmental precautions**

Contain spill with earth or sand.

If the product has entered a watercourse in sewers or has contaminated soil or vegetation, notify it to the authorities.

Discharge the remains in compliance with the regulations

### **6.3. Methods and material for containment and cleaning up**

6.3.1 For containment:

Rapidly recover the product, wear a mask and protective clothing

Recover the product for reuse, if possible, or for removal. Possibly absorb it with inert material.

Prevent it from entering the sewer system.

6.3.2 For cleaning up:

After wiping up, wash with water the area and materials involved

6.3.3 Other information:

None in particular.

**6.4. Reference to other sections**

Refer to paragraphs 8 and 13 for more information

**SECTION 7. Handling and storage****7.1. Precautions for safe handling**

Avoid contact and inhalation of vapors

At work do not eat or drink.

Wear protective gloves/protective clothing/eye protection/face protection.

See also paragraph 8 below.

**7.2. Conditions for safe storage, including any incompatibilities**

Keep in original container closed tightly. Do not store in open or unlabeled containers.

Keep containers upright and safe by avoiding the possibility of falls or collisions.

Store in a cool place, away from sources of heat and direct exposure of sunlight.

**7.3. Specific end use(s)**

Industrial Manufacturing:

Handle with extreme caution.

Store in a well ventilated place away from heat sources.

Private households (= general public = consumers):

Handle with care.

Store in ventilated place away from heat sources,

Keep the container tightly closed.

Public domain (administration, education, entertainment, services, craftsmen):

Handle with care. Store in a ventilated area and away from heat, keep the container tightly closed.

**SECTION 8. Exposure controls/personal protection****8.1. Control parameters**

Related to contained substances:

Propan-2-ol:

TLV: TWA 200 ppm 400 ppm as STEL A4 (not classifiable as a human carcinogen); (ACGIH 2004).

MAK: 200 ppm 500 mg/m peak limitation Category: II (2); Risk group for pregnancy: C; (DFG 2004).

ethanol:

Component CAS-No. Value Control parameters

Basis

Ethanol-17-64 TWA 5 ppm 1.000

1.920 mg/m<sup>3</sup>

UK. EH40 WEL-Workplace Exposure Limits

Remarks Where no specific short-term exposure limit is listed, a figure three times the long-term exposure should be used

- Substance: Propan-2-ol

DNEL

Systemic effects Long term Workers inhalation = 500 (mg/m<sup>3</sup>)

Systemic effects Long term Workers dermal = 888 (mg/kg bw/day)

Systemic effects Long term Consumers inhalation = 89 (mg/m<sup>3</sup>)

Systemic effects Long term Consumers dermal = 26 (mg/kg bw/day)

Systemic effects Long term Consumers oral = 26 (mg/kg bw/day)

PNEC

Sweet water = 140,9 (mg/l)

---

sediment Sweet water = 552 (mg/kg/sediment)  
Sea water = 140,9 (mg/l)  
sediment Sea water = 552 (mg/kg/sediment)  
intermittent emissions = 140,9 (mg/l)  
STP = 2251 (mg/l)  
ground = 28 (mg/kg ground)

- Substance: Sodium Lauryl Ether sulfate

DNEL

Systemic effects Long term Workers inhalation = 175 (mg/m<sup>3</sup>)  
Systemic effects Long term Workers dermal = 2750 (mg/kg bw/day)  
Systemic effects Long term Consumers inhalation = 52 (mg/m<sup>3</sup>)  
Systemic effects Long term Consumers dermal = 1650 (mg/kg bw/day)  
Systemic effects Long term Consumers oral = 15 (mg/kg bw/day)

PNEC

Sweet water = 0,24 (mg/l)  
sediment Sweet water = 5,45 (mg/kg/sediment)  
Sea water = 0,02 (mg/l)  
sediment Sea water = 0,54 (mg/kg/sediment)  
intermittent emissions = 0,07 (mg/l)  
STP = 10000 (mg/l)  
ground = 0,946 (mg/kg ground)

- Substance: ethanol

DNEL

Systemic effects Long term Workers inhalation = 950 (mg/m<sup>3</sup>)  
Systemic effects Long term Workers dermal = 343 (mg/kg bw/day)  
Systemic effects Long term Consumers inhalation = 114 (mg/m<sup>3</sup>)  
Systemic effects Long term Consumers dermal = 206 (mg/kg bw/day)  
Systemic effects Long term Consumers oral = 87 (mg/kg bw/day)

PNEC

Sweet water = 0,96 (mg/l)  
sediment Sweet water = 3,6 (mg/kg/sediment)  
Sea water = 0,79 (mg/l)  
sediment Sea water = 2,9 (mg/kg/sediment)  
intermittent emissions = 2,75 (mg/l)  
STP = 580 (mg/l)  
ground = 0,63 (mg/kg ground)

- Substance: tetrasodium ethylenediaminetetraacetate

DNEL

Systemic effects Long term Workers inhalation = 1,5 (mg/m<sup>3</sup>)  
Systemic effects Long term Consumers inhalation = 0,6 (mg/m<sup>3</sup>)  
Systemic effects Long term Consumers oral = 25 (mg/kg bw/day)  
Systemic effects Short term Workers inhalation = 2,5 (mg/m<sup>3</sup>)  
Systemic effects Short term Consumers inhalation = 1,2 (mg/m<sup>3</sup>)  
Local effects Long term Workers inhalation = 1 (mg/m<sup>3</sup>)  
Local effects Long term Consumers inhalation = 0,6 (mg/m<sup>3</sup>)  
Local effects Short term Workers inhalation = 3 (mg/m<sup>3</sup>)  
Local effects Short term Consumers inhalation = 1,2 (mg/m<sup>3</sup>)

PNEC

Sweet water = 2,2 (mg/l)  
sediment Sweet water = 0,22 (mg/kg/sediment)  
Sea water = 0,22 (mg/l)  
intermittent emissions = 1,2 (mg/l)  
STP = 43 (mg/l)

---

---

ground = 0,72 (mg/kg ground)

- Substance:  $\alpha$ -Hexylcinnamaldehyde

DNEL

Systemic effects Long term Workers inhalation = 0,000078 (mg/m<sup>3</sup>)

Systemic effects Short term Workers inhalation = 0,00628 (mg/m<sup>3</sup>)

PNEC

Sweet water = 0,03 (mg/l)

sediment Sweet water = 47,7 (mg/kg/sediment)

Sea water = 0,003 (mg/l)

sediment Sea water = 4,77 (mg/kg/sediment)

ground = 9,51 (mg/kg ground)

- Substance: benzyl acetate

DNEL

Systemic effects Long term Workers inhalation = 21,9 (mg/m<sup>3</sup>)

Systemic effects Long term Workers dermal = 6,25 (mg/kg bw/day)

Systemic effects Long term Consumers inhalation = 5,5 (mg/m<sup>3</sup>)

Systemic effects Long term Consumers dermal = 3,125 (mg/kg bw/day)

Systemic effects Long term Consumers oral = 3,125 (mg/kg bw/day)

- Substance: Citronellol

DNEL

Systemic effects Long term Workers inhalation = 161,6 (mg/m<sup>3</sup>)

- Substance: Hexyl salicylate

DNEL

Systemic effects Long term Workers inhalation = 0,79 (mg/m<sup>3</sup>)

Systemic effects Long term Workers dermal = 2083 (mg/kg bw/day)

Systemic effects Short term Workers inhalation = 0,79 (mg/m<sup>3</sup>)

Systemic effects Short term Workers dermal = 2083 (mg/kg bw/day)

- Substance: Tetrahydro-2-isobutyl-4-methyl-pyran-4-ol

DNEL

Systemic effects Long term Workers inhalation = 12,2 (mg/m<sup>3</sup>)

Systemic effects Long term Workers dermal = 3,47 (mg/kg bw/day)

Systemic effects Long term Consumers inhalation = 3,62 (mg/m<sup>3</sup>)

Systemic effects Long term Consumers dermal = 2,08 (mg/kg bw/day)

Systemic effects Long term Consumers oral = 1,04 (mg/kg bw/day)

- Substance: Geraniol

DNEL

Systemic effects Long term Workers inhalation = 161,6 (mg/m<sup>3</sup>)

- Substance: 1-(2,3,8,8-Tetramethyl-1,2,3,4,5,6,7,8-octahydronaphthalen-2-yl)ethanone

DNEL

Systemic effects Long term Workers inhalation = 1,76 (mg/m<sup>3</sup>)

Systemic effects Long term Workers dermal = 1,73 (mg/kg bw/day)

Systemic effects Short term Workers inhalation = 1,76 (mg/m<sup>3</sup>)

Systemic effects Short term Workers dermal = 1,73 (mg/kg bw/day)

PNEC

Sweet water = 0,0028 (mg/l)

sediment Sweet water = 3,73 (mg/kg/sediment)

Sea water = 0,00028 (mg/l)

sediment Sea water = 0,75 (mg/kg/sediment)

ground = 0,705 (mg/kg ground)

---

- Substance: 3-(4-Isobutyl-2-methylphenyl)propanal

PNEC

Sweet water = 0,0064 (mg/l)

sediment Sweet water = 1,3 (mg/kg/sediment)

Sea water = 0,00064 (mg/l)

sediment Sea water = 0,13 (mg/kg/sediment)

intermittent emissions = 0,0101 (mg/l)

STP = 1 (mg/l)

ground = 0,256 (mg/kg ground)

- Substance: 1-(1,2,3,5,6,7,8,8a-octahydro-2,3,8,8-tetramethyl-2-naphthyl)ethan-1-one

DNEL

Systemic effects Short term Workers inhalation = 1,76 (mg/m<sup>3</sup>)

Systemic effects Short term Workers dermal = 1,73 (mg/kg bw/day)

PNEC

Sweet water = 0,0028 (mg/l)

sediment Sweet water = 3,73 (mg/kg/sediment)

Sea water = 0,00028 (mg/l)

sediment Sea water = 0,75 (mg/kg/sediment)

ground = 0,705 (mg/kg ground)

- Substance: 2,6-di-tert-butyl-p-cresol

DNEL

Systemic effects Long term Workers inhalation = 3,5 (mg/m<sup>3</sup>)

Systemic effects Long term Workers dermal = 8,3 (mg/kg bw/day)

Systemic effects Long term Consumers inhalation = 1,74 (mg/m<sup>3</sup>)

Systemic effects Long term Consumers dermal = 5 (mg/kg bw/day)

Systemic effects Long term Consumers oral = 0,25 (mg/kg bw/day)

## 8.2. Exposure controls

Appropriate engineering controls:

Industrial Manufacturing:

No specific monitoring foreseen

Private households (= general public = consumers):

No specific checks planned

Public domain (administration, education, entertainment, services, craftsmen):

No specific monitoring foreseen

Individual protection measures:

(a) Eye / face protection

Not needed for normal use.

(b) Skin protection

(i) Hand protection

Handle with gloves. Gloves must be checked before use. Use a technique suitable for removing gloves (without touching the outer surface of the glove) to avoid the skin contact with this product. Dispose of contaminated gloves after use in accordance with

---

current legislation and good laboratory practices. Wash and dry your hands.

The selected protective gloves have to satisfy the requirements of EU directive 89/686 / EEC e the resulting EN 374 standards.

Full contact

Material: Nitrile rubber

minimum thickness: 0.11 mm

breakthrough time: 480 min

The choice of an appropriate glove depends not only on the material but also on other quality characteristics which vary from one manufacturer to another.

For the choice of the type of gloves to use, consult the supplier / manufacturer of the gloves.

Observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves.

(ii) Other

Wear normal work clothing.

(c) Respiratory protection

Not needed for normal use.

(d) Thermal hazards

No hazard to report

Environmental exposure controls:

Use according to good working practices to avoid pollution into the environment.

## SECTION 9. Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical and chemical properties	Value	Determination method
Physical state	Gel	
Colour	Blue	
Odour	Characteristic	
Odour threshold	not determined	
Melting point/freezing point	not determined	
Boiling point or initial boiling point and boiling range	not determined	
Flammability	nonflammable	
Lower and upper explosion limit	not determined	
Flash point	> 65 °C	ASTM D92
Auto-ignition temperature	undefined	
Decomposition temperature	not determined	
pH	6.5 - 7.5	
Kinematic viscosity	not determined	
Solubility	Completely soluble in water	
Water solubility	Completely soluble in water	
Partition coefficient n-octanol/water (log value)	not determined	
Vapour pressure	not determined	
Density and/or relative density	1,00 - 1,05 gr/cm3	
Relative vapour density	not determined	
Particle characteristics	irrelevant	

Physical and chemical properties	Value	Determination method
----------------------------------	-------	----------------------

**9.2. Other information**

Content of VOC ready to use condition: 5,11 %

**9.2.1 Information with regard to physical hazard classes****a) Explosives**

i) sensitivity to shock  
Irrilevant

ii) effect of heating under confinement  
Irrilevant

iii) effect of ignition under confinement  
Irrilevant

iv) sensitivity to impact  
Irrilevant

v) sensitivity to friction  
Irrilevant

vi) thermal stability  
Irrilevant

vii) package  
Irrilevant

**b) Flammable gases**

i) Tci / explosion limits  
Irrilevant

ii) fundamental burning velocity  
Irrilevant

**c) Aerosols**  
Irrilevant**d) Oxidising gases**  
Irrilevant**e) Gases under pressure**  
Irrilevant**f) Flammable liquids**  
Irrilevant**g) Flammable solids**

i) burning rate, or burning time as regards metal powders  
Irrilevant

---

ii) statement on whether the wetted zone has been passed

Irrilevant

h) Self-reactive substances and mixtures

i) decomposition temperature

Irrilevant

ii) detonation properties

Irrilevant

iii) deflagration properties

Irrilevant

iv) effect of heating under confinement

Irrilevant

v) explosive power, if applicable

Irrilevant

i) Pyrophoric liquids

Irrilevant

j) Pyrophoric solids

i) statement on whether spontaneous ignition occurs when poured or within five minutes thereafter, as regards solids in powder form

Irrilevant

ii) statement on whether pyrophoric properties could change over time

Irrilevant

k) Self-heating substances and mixtures

i) statement on whether spontaneous ignition occurs and the maximum temperature rise obtained

Irrilevant

ii) results of screening tests referred to in section 2.11.4.2 of Annex I to Regulation (EC) No 1272/2008, if relevant and available

Irrilevant

l) Substances and mixtures, which emit flammable gases in contact with water. The following information may be provided

i) identity of the emitted gas, if known

Irrilevant

ii) statement on whether the emitted gas ignites spontaneously

Irrilevant

iii) gas evolution rate

Irrilevant

m) Oxidising liquids

Irrilevant

n) Oxidizing solids

Irrilevant

---

o) Organic peroxides

i) decomposition temperature

Irrilevant

ii) detonation properties

Irrilevant

iii) deflagration properties

Irrilevant

iv) effect of heating under confinement

Irrilevant

v) explosive power

Irrilevant

p) Corrosive to metals

i) metals that are corroded by the substance or mixture

Irrilevant

ii) corrosion rate and statement on whether it refers to steel or aluminium

Irrilevant

iii) reference to other sections of the safety data sheet with regard to compatible or incompatible materials

Irrilevant

q) Desensitised explosives

i) desensitising agent used

Irrilevant

ii) exothermic decomposition energy

Irrilevant

iii) corrected burning rate (Ac)

Irrilevant

iv) explosive properties of the desensitised explosive in that state

Irrilevant

**9.2.2 Other safety characteristics**

a) mechanical sensitivity

Irrilevant

b) self-accelerating polymerisation temperature

Irrilevant

c) formation of explosible dust/air mixtures

Irrilevant

d) acid/alkaline reserve

Irrilevant

---

- e) evaporation rate  
Irrilevant
- f) miscibility  
Irrilevant
- g) conductivity  
Irrilevant
- h) corrosiveness  
Irrilevant
- i) gas group  
Irrilevant
- j) redox potential  
Irrilevant
- k) radical formation potential  
Irrilevant
- l) photocatalytic properties  
Irrilevant

## **SECTION 10. Stability and reactivity**

### **10.1. Reactivity**

No reactivity hazards

### **10.2. Chemical stability**

No hazardous reaction when handled and stored according to provisions.

### **10.3. Possibility of hazardous reactions**

There are no hazardous reactions

### **10.4. Conditions to avoid**

Nothing to report

### **10.5. Incompatible materials**

It can generate inflammable gases to contact with elementary metals, nitrides, inorganic sulfide, strong reducing agents.

It can generate toxic gases to contact with inorganic sulfide, strong reducing agents.

### **10.6. Hazardous decomposition products**

Does not decompose when used for intended uses.

---

**SECTION 11. Toxicological information****11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**

ATE(mix) oral = 12.173,2 mg/kg  
ATE(mix) dermal = 222.222,2 mg/kg  
ATE(mix) inhal =  $\infty$

(a) acute toxicity: ethanol: LD50 Oral-rat-7.060 mg/kg  
Remarks: Lungs, Thorax, or Respiration: Other changes.  
LC50 Inhalation-rat-10:0-20000 ppm

$\alpha$ -Hexylcinnamaldehyde: Oral (rat) LD50: 2450 mg/kg  
(b) skin corrosion/irritation: Propan-2-ol: Skin-rabbit

Result: Mild skin irritation

Sodium Lauryl Ether sulfate: Acute effects: contact with eyes will cause irritation; symptoms may include: redness, edema, pain and tears.

Through contact with the skin has irritation with erythema, edema, dryness and cracking.

ethanol: Skin-rabbit

Result: Irritating to skin. -12:0 am

(c) serious eye damage/irritation: If brought into contact with eyes, the product, causes significant irritations which may last for more than 24 hours.

ethanol: Eyes-rabbit

Result: Mild eye irritation-12:0 am

(Draize Test)

Propan-2-ol: Eyes-rabbit

Result: Eye irritation- 24 h

(d) respiratory or skin sensitisation: based on available data, the classification criteria are not met.

(e) germ cell mutagenicity: based on available data, the classification criteria are not met.

(f) carcinogenicity: based on available data, the classification criteria are not met.

(g) reproductive toxicity: ethanol: Reproductive toxicity-Human-female-Oral

Effects on Newborn: Apgar score (human only). Effects on Newborn: Other measures or neonatal effects.

Effects on Newborn: Drug dependence.

(h) specific target organ toxicity (STOT) single exposure: based on available data, the classification criteria are not met.

(i) specific target organ toxicity (STOT) repeated exposure based on available data, the classification criteria are not met.

(j) aspiration hazard: based on available data, the classification criteria are not met.

Health hazards:

Contact with eyes: Accidental contact of the product with the eyes can cause irritation.

Skin contact: The product is not an irritant. Repeated and prolonged direct contact can degrease and irritate the skin causing dermatitis in some cases.

Ingestion: The ingested product can cause irritation of the mucous membranes of the throat and digestive system with consequent abnormal digestive symptoms and intestinal disorders.

Inhalation: Prolonged exposure to vapors or mists of the product can cause irritation to the respiratory tract.

Related to contained substances:

Propan-2-ol:

ROUTES of EXPOSURE: the substance can be absorbed into the body by inhalation of its fumes.

INHALATION RISK: A harmful contamination of the air will be reached quite slowly due to evaporation of the substance at 20 C; However, for spraying or scattering, much more quickly.

Effects of short-term exposure: the substance is irritating to the eyes and the respiratory tract the substance may cause effects on the central nervous system, causing depression. Much greater exposure to the OEL may lead to unconsciousness.

Effects of REPEATED EXPOSURE or long term: the liquid degreasing the skin features.

ACUTE HAZARDS/Symptoms INHALATION Cough. Vertigo. Drowsiness. Headaches. Sore throat. See If Swallowed.  
CUTE CUTE.

EYE Redness.

INGESTION abdominal pain. Difficulty in breathing. Nausea. State of unconsciousness. Vomiting. (Further see

inhalation).

N O T and use of alcoholic beverages enhances the harmful effect.

LD50 (rat) Oral (mg/kg body weight) = 2100

LD50 Dermal (rat or rabbit) (mg/kg body weight) = 2100

CL50 Inhalation (rat) vapour/dust/mist/fume (mg/l/4h) or gas (ppmV/4h) = 29

Alcohols, C13-15, branched and linear, ethoxylated:

LD50 (rat) Oral (mg/kg body weight) > 300

Sodium Lauryl Ether sulfate:

LD50 (alcohols, C12-14, ethoxylated, sulfated, sodium salts; CAS No.: 68891-38-3)

Via Inhalation Administration:

Test species: rat

Value: 4100 mg/kg

Specification: LD50 (alcohols, C12-14, ethoxylated, sulfated, sodium salts; CAS No.: 68891-38-3)

Via Dermal intake:

Test species: rat

Value: > 2000 mg/kg

LD50 (rat) Oral (mg/kg body weight) = 2000

LD50 Dermal (rat or rabbit) (mg/kg body weight) = 2000

CL50 Inhalation (rat) vapour/dust/mist/fume (mg/l/4h) or gas (ppmV/4h) = 4100

ethanol:

ROUTES of EXPOSURE: the substance can be absorbed into the body by inhalation of its fumes and ingestion.

INHALATION RISK: A harmful contamination of the air will be reached quite slowly due to evaporation of the substance at 20 C.

Effects of short-term exposure: the substance is irritating to the eyes. Inhalation of high vapour can cause irritation of the eyes and respiratory tract. The substance may cause effects on the central nervous system effects of REPEATED EXPOSURE or long term: the liquid degreasing the skin features. The substance may have an effect on the high central nervous system respiratory tract, causing irritation, headaches, fatigue and lack of concentration. See Notes.

ACUTE HAZARDS/Symptoms INHALATION Cough. Headaches. Fatigue. Drowsiness.

CUTE CUTE.

EYE Redness. Pain. Burning.

SWALLOWED burning sensation. Headaches. Confusion. Vertigo. State of unconsciousness.

N O T and consumption of ethanol during pregnancy can have adverse effects on the unborn child. Chronic ethanol ingestion can cause cirrhosis of the liver.

LD50 (rat) Oral (mg/kg body weight) = 7060

LD50 Dermal (rat or rabbit) (mg/kg body weight) = 20000

CL50 Inhalation (rat) vapour/dust/mist/fume (mg/l/4h) or gas (ppmV/4h) = 20000

$\alpha$ -Hexylcinnamaldehyde:

LD50 (rat) Oral (mg/kg body weight) = 2450

1,2-benzisothiazol-3(2H)-one:

LD50 (rat) Oral (mg/kg body weight) = 1020

## 11.2. Information on other hazards

No data available.

## SECTION 12. Ecological information

---

**12.1. Toxicity**

Related to contained substances:

Propan-2-ol:

Toxicity to fish LC50-Pimephales promelas (fathead minnow)-9, 640.00 mg/l-96 h

Toxicity to daphnia and other aquatic invertebrates

-EC50 Daphnia magna (Water flea)-5, 102.00 mg/l- 24 h

EC50 Immobilization-Daphnia magna (Water flea)-6.851 mg/l- 24h

C(E)L50 (mg/l) = 5102 1

1

Alcohols, C13-15, branched and linear, ethoxylated:

C(E)L50 (mg/l) = 1

Sodium Lauryl Ether sulfate:

LC50 (alcohols, C12-14, ethoxylated, sulfated, sodium salts; CAS No.: 68891-38-3)

Parametro: Fish

Danio Rerio

Value = 7.1 mg/l

For. test: 96 h

Specification: EC50 (alcohols, C12-14, ethoxylated, sulfated, sodium salts; CAS No.: 68891-38-3)

Parametro: Daphnia

Daphnia magna

Value = 7.2 mg/l

For. test: 48 h

Specification: EC50 (alcohols, C12-14, ethoxylated, sulfated, sodium salts; CAS No.: 68891-38-3)

Parametro: Algae

Scenedesmus subspicatus

Value = 27 mg/l

C(E)L50 (mg/l) = 7,1 1

1

ethanol:

C(E)L50 (mg/l) = 11200

 $\alpha$ -Hexylcinnamaldehyde:

Freshwater Fish Toxicity: acute LC50 &gt;1-10 mg/L

Freshwater Invertebrates Toxicity: acute EC &lt;1 mg/L

Algal Toxicity: acute EC &lt;1 mg/L.

C(E)L50 (mg/l) = 0,99

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1):

Acute toxicity to fish

The material is very toxic to aquatic organisms (LC50 / EC50 / IC50 below 1 mg / l for the most sensitive species).

LC50, Oncorhynchus mykiss (rainbow trout), flow-through test, 96 Hour, 0.19 mg / l, OECD Test Guideline 203 or equivalent

Acute toxicity to aquatic invertebrates

EC50, Daphnia magna (Water flea), Flow-through test, 48 h, 0.16 mg / l, OECD Test Guideline 202 or equivalent

Acute toxicity to algae / aquatic plants

EC50, Pseudokirchneriella subcapitata (green algae), 72 Hour, 0.027 mg / l, OECD Test Guideline 201 or equivalent

NOEC, Skeletonema costatum, Static test, 72 h, Growth rate, 0.0014 mg / l

Chronic toxicity to fish

NOEC, Rainbow trout (Oncorhynchus mykiss), flow, 14 d, 0.05 mg / l

Chronic toxicity to aquatic invertebrates

NOEC, Daphnia magna, Flow-through test, 21 d, 0.1 mg / l

100

NOEC (mg/l) = 0,05 100

1,2-benzisothiazol-3(2H)-one:  
C(E)L50 (mg/l) = 0,8

Use according to good working practices to avoid pollution into the environment.

### **12.2. Persistence and degradability**

Related to contained substances:  
Sodium Lauryl Ether sulfate:  
Easily biodegradable

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1):

Biodegradation (aquatic metabolism): 5-chloro-2-methyl-4-isothiazolin-3-one (CMIT):

t  $\frac{1}{2}$  anaerobic = 0.2 days. t  $\frac{1}{2}$  aerobic = 0.38 - 1.3 days. 2-methyl-4-isothiazolin-3-one (MIT): aerobic t  $\frac{1}{2}$  = 0.38 - 1.4 days

Biodegradability: Considered to be rapidly degradable. The product is not readily biodegradable according to OECD / EC criteria.

Biodegradation: <50%

Exposure time: 10 d

Photodegradation

Atmospheric half-life: 0.38 - 1.3 d

12.3 Bioaccumulative potential

Partition coefficient: n-octanol / water (log Pow): 0.401 Method not specified.

### **12.3. Bioaccumulative potential**

Related to contained substances:  
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1):  
Low potential for bioconcentration (FBC or Log Pow < 100 < 3).

### **12.4. Mobility in soil**

No data available.

### **12.5. Results of PBT and vPvB assessment**

Based on the available data, no PBT or vPvB substances are present in accordance with Regulation (EC) 1907/2006, annex XIII

### **12.6. Endocrine disrupting properties**

Based on available data, there are no substances that interfere with the Endocrine System in accordance with Regulation (EU) 2017/2100

### **12.7. Other adverse effects**

No adverse effects

## **SECTION 13. Disposal considerations**

### **13.1. Waste treatment methods**

Do not reuse empty containers. Dispose of them in accordance with the regulations in force. Any remaining product should be disposed of according to applicable regulations by addressing to authorized companies.  
Recover if possible. Operate according to local or national regulations

## **SECTION 14. Transport information**

### **14.1. UN number or ID number**

Not included in the scope of application regulations concerning the transport of dangerous goods: by road (ADR); by rail (RID); by air (ICAO / IATA); by sea (IMDG).

### **14.2. UN proper shipping name**

None

### **14.3. Transport hazard class(es)**

None

### **14.4. Packing group**

None

### **14.5. Environmental hazards**

None

### **14.6. Special precautions for user**

No data available.

### **14.7. Maritime transport in bulk according to IMO instruments**

It is not intended to carry bulk

## **SECTION 15. Regulatory information**

### **15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Substances in the Candidate List (REACH Article 59)

Based on available data, no SVHC substances are present

### **15.2. Chemical safety assessment**

The supplier has made an assessment of chemical safety

## **SECTION 16. Other information**

### **16.1. Other information**

Points modified compared to previous release: 2.2. Label elements, 2.3. Other hazards, 3.2 Mixtures, 8.1. Control parameters, 9.2. Other information, 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008,

---

12.1. Toxicity, 12.2. Persistence and degradability, 12.3. Bioaccumulative potential, 12.5. Results of PBT and vPvB assessment, 12.6. Endocrine disrupting properties, 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Description of the hazard statements exposed to point 3

- H225 = Highly flammable liquid and vapour.
- H319 = Causes serious eye irritation.
- H336 = May cause drowsiness or dizziness.
- H302 = Harmful if swallowed.
- H318 = Causes serious eye damage.
- H412 = Harmful to aquatic life with long lasting effects.
- H315 = Causes skin irritation.
- H317 = May cause an allergic skin reaction.
- H411 = Toxic to aquatic life with long lasting effects.
- H301 = Toxic if swallowed.
- H310 = Fatal in contact with skin.
- H314 = Causes severe skin burns and eye damage.
- H330 = Fatal if inhaled.
- H400 = Very toxic to aquatic life.
- H410 = Very toxic to aquatic life with long lasting effects.

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Classification according to Regulation (EC) Nr. 1272/2008

H319 - Causes serious eye irritation. Classification procedure: Calculation method

Main normative references:

Directive 1999/45/EC  
Directive 2001/60/EC  
Regulation 1272/2008/EC  
Regulation 2010/453/EC

\*\* The information contained herein is based on our knowledge at the date above.

Related solely to the product and do not constitute a guarantee of a particular quality.

It is the duty of the user to ensure that these are appropriate and complete information regarding the specific use intended.

This data sheet cancels and replaces any previous edition.

---