

SECTION 1. Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Product code : Hygienfresh Detergente Piumacare

Trades code : A39-540

Product line: Hygienfresh

UFI: A801-6044-700R-FPQD

1.2. Relevant identified uses of the substance or mixture and uses advised against

Deo concentrated detergent

Sectors of use:

Industrial Manufacturing[SU3], Private households (= general public = consumers)[SU21], Public domain (administration, education, entertainment, services, craftsmen)[SU22]

Uses advised against

Do not use for purposes other than those listed

1.3. Details of the supplier of the safety data sheet

Tintolav s.r.l. - Via M. D' Antona 7 - 10028 Trofarello (TO) Tel. 011/649.68.27 Fax 011/649.67.42

Email: info@tintolav.com - Sito internet: www.tintolav.com

Email tecnico competente: a.conedera@tintolav.com

National contact: Malta: Emergency Ambulance 112

Accident & Emergency Department 2545 4030

1.4. Emergency telephone number

The UK National Poisons Emergency number +44 (0)870 600 6266

London: Emergency 24 hour telephone +44 (0) 207188 0100

SECTION 2. Hazards identification**2.1. Classification of the substance or mixture**

2.1.1 Classification according to Regulation (EC) No 1272/2008:

Pictograms:

GHS07

Hazard Class and Category Code(s):

Skin Irrit. 2, Eye Irrit. 2

Hazard statement Code(s):

H315 - Causes skin irritation.

H319 - Causes serious eye irritation.

If brought into contact with eyes, the product causes significant irritations which may last for more than 24 hours, if brought into contact with skin, it causes significant inflammation with erythema, scabs, or edema

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008:

Issued on 11/24/2021 - Rel. # 7 on 11/24/2021

2 / 12

In conformity to Regulation (EU) 2020/878

Pictogram, Signal Word Code(s):
GHS07 - Warning



Hazard statement Code(s):
H315 - Causes skin irritation.
H319 - Causes serious eye irritation.

Supplemental Hazard statement Code(s):
EUH208 - Contains reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1). May produce an allergic reaction.

Precautionary statements:

General

P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children.

Prevention

P264 - Wash your hand thoroughly after handling.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

Response

P302+P352 - IF ON SKIN: Wash with plenty of water and soap.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P332+P313 - If skin irritation occurs: Get medical advice/attention.

P337+P313 - If eye irritation persists: Get medical advice/attention.

Contains (Reg.EC 648/2004):

5% < 15% anionic surfactants, < 5% perfumes, Miscela di: 5-cloro-2-metil-2H-isotiazol-3-one [EC no. 247-500-7]; 2-metil-2H-isotiazol-3-one [EC no. 220-239-6] (3:1), Dye, non-ionic surfactants, Linalool

Content of VOC ready to use condition: 1,01 %

UFI: A801-6044-700R-FPQD

2.3. Other hazards

The substance / mixture NOT contains substances PBT/vPvB according to Regulation (EC) No 1907/2006, Annex XIII

No information on other hazards

SECTION 3. Composition/information on ingredients

3.1 Substances

Irrilevant

3.2 Mixtures

Refer to paragraph 16 for full text of hazard statements

Substance	Concentration[w/w]	Classification	Index	CAS	EINECS	REACH
Dodecylbenzenesulphonic acid, compound with 2,2',2"nitrilotriethanol (1:1).	>= 5 < 15%	Skin Irrit. 2, H315; Eye Irrit. 2, H319 ATE oral = 1.653,0 mg/kg	ND	27323-41-7	248-406-9	NR

Substance	Concentration[w/w]	Classification	Index	CAS	EINECS	REACH
		ATE dermal = 4.199,0 mg/kg				
Coconut diethanolamide	$\geq 1 < 3\%$	Skin Irrit. 2, H315; Eye Dam. 1, H318 ATE oral = 5.000,0 mg/kg	ND	68603-42-9	271-657-0	NR
Alcohols, C13-15, branched and linear, ethoxylated	$\geq 1 < 5\%$	Acute Tox. 4, H302; Eye Dam. 1, H318; Aquatic Chronic 3, H412 Limits: Eye Irrit. 2, H319 %C ≤ 10 ; Eye Dam. 1, H318 %C > 10 ; 1 1 ATE oral = 300,0 mg/kg	ND	157627-86-6	ND	NR
Sodium dodecylbenzenesulfonate	$\geq 1 < 5\%$	Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Irrit. 2, H315; Eye Irrit. 2, H319 ATE oral = 438,0 mg/kg ATE dermal = 2.000,0 mg/kg	ND	25155-30-0	246-680-4	NR
ethanol	$\geq 0,1 < 1\%$	Flam. Liq. 2, H225 ATE oral = 7.060,0 mg/kg ATE dermal = 20.000,0 mg/kg ATE inhal = 20.000,0mg/l/4 h	603-002-00-5	64-17-5	200-578-6	01-2119457 610-43

SECTION 4. First aid measures

4.1. Description of first aid measures

Inhalation:

Air the area. Move immediately the contaminated patient from the area and keep him at rest in a well ventilated area. If you feel unwell seek medical advice.

Direct contact with skin (of the pure product):

Take contaminated clothing Immediately off.

Wash immediately with plenty of running water and possibly with soap, the areas of the body that have, or are only suspected to have, come in contact with the product.

In case of contact with skin, wash immediately with Water and soap.

Direct contact with eyes (of the pure product):

Wash immediately and thoroughly with running water, keeping eyelids open for at least 10 minutes, then protect your eyes with a dry sterile gauze. Seek medical advice immediately

Do not use eye drops or ointments of any kind before the examination or advice from an oculist.

Ingestion:

Not hazardous. It's possible to give activated charcoal in water or liquid paraffin medicine

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

If skin irritation occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

If medical advice is needed, have product container or label at hand.

SECTION 5. Firefighting measures

5.1. Extinguishing media

Advised extinguishing agents:

Water spray, CO₂, foam, dry chemical, depending on the materials involved in the fire.

Extinguishing means to avoid:

Water jets. Use water jets only to cool the surfaces of the containers exposed to fire.

5.2. Special hazards arising from the substance or mixture

No data available.

5.3. Advice for firefighters

Use protection for the breathing apparatus

Safety helmet and full protective suit.

The spray water can be used to protect the people involved in the extinction

You may also use selfrespirator, especially when working in confined and poorly ventilated area and if you use halogenated extinguishers (Halon 1211 fluobrene, Solkan 123, NAF, etc...)

Keep containers cool with water spray

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel:

Leave the area surrounding the spill or release. Do not smoke

Wear mask, gloves and protective clothing.

6.1.2 For emergency responders:

Wear mask, gloves and protective clothing. Suitable: LaTeX, nitrile, PVC

Eliminate all unguarded flames and possible sources of ignition. No smoking.

Provision of sufficient ventilation.

Evacuate the danger area and, in case, consult an expert.

6.2. Environmental precautions

Contain spill with earth or sand.

If the product has entered a watercourse in sewers or has contaminated soil or vegetation, notify it to the authorities.

Discharge the remains in compliance with the regulations

6.3. Methods and material for containment and cleaning up

6.3.1 For containment:

Rapidly recover the product, wear a mask and protective clothing

Recover the product for reuse, if possible, or for removal. Possibly absorb it with inert material.
Prevent it from entering the sewer system.

6.3.2 For cleaning up:
After wiping up, wash with water the area and materials involved

6.3.3 Other information:
None in particular.

6.4. Reference to other sections

Refer to paragraphs 8 and 13 for more information

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Avoid contact and inhalation of vapors
Wear protective gloves/protective clothing/eye protection/face protection.
At work do not eat or drink.
See also paragraph 8 below.

7.2. Conditions for safe storage, including any incompatibilities

Keep in original container closed tightly. Do not store in open or unlabeled containers.
Keep containers upright and safe by avoiding the possibility of falls or collisions.
Store in a cool place, away from sources of heat and direct exposure of sunlight.

7.3. Specific end use(s)

Industrial Manufacturing:
Handle with extreme caution.
Store in a well ventilated place away from heat sources.

Private households (= general public = consumers):
Handle with care.
Store in ventilated place away from heat sources,
Keep the container tightly closed.

Public domain (administration, education, entertainment, services, craftsmen):
Handle with care. Store in a ventilated area and away from heat, keep the container tightly closed.

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Related to contained substances:
ethanol:
Component CAS-No. Value Control parameters
Basis
Ethanol-17-64 TWA 5 ppm 1.000
1.920 mg/m³
UK. EH40 WEL-Workplace Exposure Limits
Remarks Where no specific short-term exposure limit is listed, a figure three times the long-term exposure should be used

- Substance: Coconut diethanolamide
DNEL
Systemic effects Long term Workers inhalation = 73,4 (mg/m³)
Systemic effects Long term Workers dermal = 4,16 (mg/kg bw/day)

Systemic effects Long term Consumers inhalation = 21,73 (mg/m³)
Systemic effects Long term Consumers dermal = 2,5 (mg/kg bw/day)
Systemic effects Long term Consumers oral = 6,25 (mg/kg bw/day)
Local effects Long term Workers dermal = 0,09 (mg/kg bw/day)
Local effects Long term Consumers dermal = 0,0562 (mg/kg bw/day)
PNEC
Sweet water = 0,007 (mg/l)
sediment Sweet water = 0,195 (mg/kg/sediment)
Sea water = 0,001 (mg/l)
sediment Sea water = 0,019 (mg/kg/sediment)
intermittent emissions = 0,024 (mg/l)
STP = 830 (mg/l)
ground = 0,035 (mg/kg ground)

- Substance: ethanol

DNEL

Systemic effects Long term Workers inhalation = 950 (mg/m³)
Systemic effects Long term Workers dermal = 343 (mg/kg bw/day)
Systemic effects Long term Consumers inhalation = 114 (mg/m³)
Systemic effects Long term Consumers dermal = 206 (mg/kg bw/day)
Systemic effects Long term Consumers oral = 87 (mg/kg bw/day)
PNEC
Sweet water = 0,96 (mg/l)
sediment Sweet water = 3,6 (mg/kg/sediment)
Sea water = 0,79 (mg/l)
sediment Sea water = 2,9 (mg/kg/sediment)
intermittent emissions = 2,75 (mg/l)
STP = 580 (mg/l)
ground = 0,63 (mg/kg ground)

8.2. Exposure controls



Appropriate engineering controls:

Industrial Manufacturing:

No specific monitoring foreseen

Private households (= general public = consumers):

No specific checks planned

Public domain (administration, education, entertainment, services, craftsmen):

No specific monitoring foreseen

Individual protection measures:

(a) Eye / face protection

When handling the pure product use safety glasses (spectacles cage) (EN 166).

(b) Skin protection

(i) Hand protection

Handle with gloves. Gloves must be checked before use. Use a technique suitable for removing gloves (without touching the outer surface of the glove) to avoid the skin contact with this product. Dispose of contaminated gloves after use in accordance with

current legislation and good laboratory practices. Wash and dry your hands.

The selected protective gloves have to satisfy the requirements of EU directive 89/686 / EEC e the resulting EN 374 standards.

Full contact

Material: Nitrile rubber

minimum thickness: 0.11 mm

breakthrough time: 480 min

The choice of an appropriate glove depends not only on the material but also on other quality characteristics which vary from one manufacturer to another.

For the choice of the type of gloves to use consult the supplier / manufacturer of the gloves.

Observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves.

(ii) Other

When handling the pure product wear full protective skin clothing.

(c) Respiratory protection

Not needed for normal use.

(d) Thermal hazards

No hazard to report

Environmental exposure controls:

Use according to good working practices to avoid pollution into the environment.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical and chemical properties	Value	Determination method
Appearance	Liquid	
Colour	Blue	
Odour	characteristic	
Odour threshold	not determined	
pH	6- 7 @ 1%	
Melting point/freezing point	not determined	
Initial boiling point and boiling range	> 65 °C	
Flash point	nonflammable	ASTM D92
Evaporation rate	irrelevant	
Flammability (solid, gas)	nonflammable	
Upper/lower flammability or explosive limits	not determined	
Vapour pressure	not determined	
Vapour density	not determined	
Relative density	0,980 - 1,020 g/cm3	
Solubility	Completely soluble in water	
Water solubility	Completely soluble in water	
Partition coefficient: n-octanol/water	not determined	
Auto-ignition temperature	not determined	
Decomposition temperature	not determined	
Viscosity	not determined	
Explosive properties	not explosive	
Oxidising properties	non-oxidizing	

Physical and chemical properties	Value	Determination method
----------------------------------	-------	----------------------

9.2. Other information

Content of VOC ready to use condition: 1,01 %

SECTION 10. Stability and reactivity**10.1. Reactivity**

No reactivity hazards

10.2. Chemical stability

No hazardous reaction when handled and stored according to provisions.

10.3. Possibility of hazardous reactions

There are no hazardous reactions

10.4. Conditions to avoid

Nothing to report

10.5. Incompatible materials

It can generate inflammable gases to contact with elementary metals, nitrides, inorganic sulfide, strong reducing agents.

It can generate toxic gases to contact with inorganic sulfide, strong reducing agents.

10.6. Hazardous decomposition products

Does not decompose when used for intended uses.

SECTION 11. Toxicological information**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**

ATE(mix) oral = 9.831,4 mg/kg

ATE(mix) dermal = 114.285,7 mg/kg

ATE(mix) inhal = ∞

(a) acute toxicity: ethanol: LD50 Oral-rat-7.060 mg/kg

Remarks: Lungs, Thorax, or Respiration: Other changes.

LC50 Inhalation-rat-10:0-20000 ppm

(b) skin corrosion/irritation: If brought into contact with the skin, the product causes significant inflammation with erythema, scabs, or edema.

Dodecylbenzenesulphonic acid, compound with 2,2',2''nitrilotriethanol (1:1): Irritating

Coconut diethanolamide: Irritating

Sodium dodecylbenzenesulfonate: Skin irritation-not irritating (2.5%), moderate irritation (5%), moderate-severe irritation (47-50%).

ethanol: Skin-rabbit

Result: Irritating to skin. -12:0 am

(c) serious eye damage/irritation: If brought into contact with eyes, the product, causes significant irritations which may last for more than 24 hours.

ethanol: Eyes-rabbit

Result: Mild eye irritation-12:0 am

(Draize Test)

Dodecylbenzenesulphonic acid, compound with 2,2',2''nitrilotriethanol (1:1): Irritating

Coconut diethanolamide: Acute Irritazione\Corrosione eyes

Sodium dodecylbenzenesulfonate: Eye irritation-mild irritation (1%); moderate irritation (5%), and severe irritation (47-50%)

(d) respiratory or skin sensitisation: Coconut diethanolamide: Non-sensitizing

(e) germ cell mutagenicity: based on available data, the classification criteria are not met.

(f) carcinogenicity: Coconut diethanolamide: IARC Group 2B carcinogen-possible carcinogenic to humans

Sodium dodecylbenzenesulfonate: IARC: no component of this product present at levels greater than or equal to 0.1% identified as known or anticipated carcinogen by IARC.

(g) reproductive toxicity: ethanol: Reproductive toxicity-Human-female-Oral

Effects on Newborn: Apgar score (human only). Effects on Newborn: Other measures or neonatal effects.

Effects on Newborn: Drug dependence.

(h) specific target organ toxicity (STOT) single exposure: based on available data, the classification criteria are not met.

(i) specific target organ toxicity (STOT) repeated exposure: Dodecylbenzenesulphonic acid, compound with 2,2',2''nitrilotriethanol (1:1): Rabbit 90-day dermal NOAEL > 5 mg/kg bw (only dose tested)

(j) aspiration hazard: based on available data, the classification criteria are not met.

Related to contained substances:

Dodecylbenzenesulphonic acid, compound with 2,2',2''nitrilotriethanol (1:1):

LD50 (rat) Oral (mg/kg body weight) = 1653

LD50 Dermal (rat or rabbit) (mg/kg body weight) = 4199

Coconut diethanolamide:

Ingestion: oral rat LD50: > 2,000 mg/kg

Eye contact: irritating to the eye (rabbit). Can cause irreversible damage to the eye.

Skin contact: moderately irritating for a single application (4 h-rabbit)

Readily biodegradable in accordance with the criteria of Directive 67/548 and subsequent modifications.

LD50 (rat) Oral (mg/kg body weight) = 5000

Alcohols, C13-15, branched and linear, ethoxylated:

LD50 (rat) Oral (mg/kg body weight) > 300

Sodium dodecylbenzenesulfonate:

LD50 (rat) Oral (mg/kg body weight) = 438

LD50 Dermal (rat or rabbit) (mg/kg body weight) = 2000

ethanol:

ROUTES of EXPOSURE: the substance can be absorbed into the body by inhalation of its fumes and ingestion.

INHALATION RISK: A harmful contamination of the air will be reached quite slowly due to evaporation of the substance at 20 C.

Effects of short-term exposure: the substance is irritating to the eyes. Inhalation of high vapour can cause irritation of the eyes and respiratory tract. The substance may cause effects on the central nervous system effects of REPEATED EXPOSURE or long term: the liquid degreasing the skin features. The substance may have an effect on the high central nervous system respiratory tract, causing irritation, headaches, fatigue and lack of concentration. See Notes.

ACUTE HAZARDS/Symptoms INHALATION Cough. Headaches. Fatigue. Drowsiness.

CUTE CUTE.

EYE Redness. Pain. Burning.

SWALLOWED burning sensation. Headaches. Confusion. Vertigo. State of unconsciousness.

N O T and consumption of ethanol during pregnancy can have adverse effects on the unborn child. Chronic ethanol

ingestion can cause cirrhosis of the liver.

LD50 (rat) Oral (mg/kg body weight) = 7060

LD50 Dermal (rat or rabbit) (mg/kg body weight) = 20000

CL50 Inhalation (rat) vapour/dust/mist/fume (mg/l/4h) or gas (ppmV/4h) = 20000

11.2. Information on other hazards

No data available.

SECTION 12. Ecological information

12.1. Toxicity

Related to contained substances:

Dodecylbenzenesulphonic acid, compound with 2,2',2''nitrilotriethanol (1:1):

C(E)L50 (mg/l) = 2,6

Coconut diethanolamide:

Acute/prolonged toxicity to fish: (83d) 2.52 mg/l (brachydanio rerio)

Acute toxicity to Aquatic Invertebrates: EC50 (12:0 am) 2.8 mg/l (daphnia Magna)

Primary: Biodegradabilit > 90% (OECD)

Easy Biodegradabilit: 60% > (manometric Tests, O2 consumption)

Theoretical O2 demand (thod) 2.52 mg O2/mg.

Chemical O2 demand (COD): 2.51 mg O2/mg.

C(E)L50 (mg/l) = 2,39

Alcohols, C13-15, branched and linear, ethoxylated:

C(E)L50 (mg/l) = 1

Sodium dodecylbenzenesulfonate:

C(E)L50 (mg/l) = 1,67

ethanol:

C(E)L50 (mg/l) = 11200

Use according to good working practices to avoid pollution into the environment.

12.2. Persistence and degradability

No data available.

12.3. Bioaccumulative potential

Related to contained substances:

Sodium dodecylbenzenesulfonate:

Bioaccumulation-28 leptomismacrochirus d -64 g/l

Bioconcentration factor (BCF): 220

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

No PBT/vPvB ingredient is present

12.6. Endocrine disrupting properties

No data available.

12.7. Other adverse effects

No adverse effects

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Do not reuse empty containers. Dispose of them in accordance with the regulations in force. Any remaining product should be disposed of according to applicable regulations by addressing to authorized companies.

Recover if possible. Operate according to local or national regulations

SECTION 14. Transport information

14.1. UN number or ID number

Not included in the scope of application regulations concerning the transport of dangerous goods: by road (ADR); by rail (RID); by air (ICAO / IATA); by sea (IMDG).

14.2. UN proper shipping name

None

14.3. Transport hazard class(es)

None

14.4. Packing group

None

14.5. Environmental hazards

None

14.6. Special precautions for user

No data available.

14.7. Maritime transport in bulk according to IMO instruments

It is not intended to carry bulk

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

REGULATION (EU) No 1357/2014 - waste:
HP4 - Irritant — skin irritation and eye damage

15.2. Chemical safety assessment

The supplier has made an assessment of chemical safety

SECTION 16. Other information**16.1. Other information**

Description of the hazard statements exposed to point 3

H315 = Causes skin irritation.
H319 = Causes serious eye irritation.
H318 = Causes serious eye damage.
H302 = Harmful if swallowed.
H412 = Harmful to aquatic life with long lasting effects.
H312 = Harmful in contact with skin.
H225 = Highly flammable liquid and vapour.

Classification based on data of all mixture components

Main normative references:

Directive 1999/45/EC
Directive 2001/60/EC
Regulation 1272/2008/EC
Regulation 2010/453/EC

** The information contained herein is based on our knowledge at the date above.

Related solely to the product and do not constitute a guarantee of a particular quality.

It is the duty of the user to ensure that these are appropriate and complete information regarding the specific use intended.

This data sheet cancels and replaces any previous edition.