

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product code : Tintolav - Appretto Okay
Trades code : A70-015
Product line: Tintolav

UFI: 4W21-V0HE-R003-X8SD

1.2. Relevant identified uses of the substance or mixture and uses advised against

Scented spray dressing

Sectors of use:

Industrial Manufacturing[SU3], Private households (= general public = consumers)[SU21], Public domain (administration, education, entertainment, services, craftsmen)[SU22]

Uses advised against

Do not use for purposes other than those listed

1.3. Details of the supplier of the safety data sheet

Tintolav s.r.l. - Via M. D' Antona 7 - 10028 Trofarello (TO) Tel. 011/649.68.27 Fax 011/649.67.42

Email: info@tintolav.com - Sito internet: www.tintolav.com

Email tecnico competente: a.conedera@tintolav.com

National contact: Malta: Emergency Ambulance 112
Accident & Emergency Department 2545 4030

1.4. Emergency telephone number

The UK National Poisons Emergency number +44 (0)870 600 6266
London: Emergency 24 hour telephone +44 (0) 207188 0100

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

2.1.1 Classification according to Regulation (EC) No 1272/2008:

Pictograms:
GHS02

Hazard Class and Category Code(s):
Flam. Aerosol 2

Hazard statement Code(s):
H223 - Flammable aerosol.
H229 - Pressurised container: May burst if heated.

Flammable aerosols, fire risk

The repeated inhalation of vapors can cause drowsiness and giddiness.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 ° C.

The aerosol containers overheated burst and can be ejected with violence from a distance and can take place a dangerous mechanism for the fire.

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008:

Pictogram, Signal Word Code(s):
GHS02 - Warning



Hazard statement Code(s):
H223 - Flammable aerosol.
H229 - Pressurised container: May burst if heated.

Supplemental Hazard statement Code(s):
EUH208 - Contains Mixture of: Methylchloroiso Thiazolinone; Methylisothiazolinone (3: 1). It can cause an allergic reaction.

Precautionary statements:

General

P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children.

Prevention

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 - Do not spray on an open flame or other ignition source.

P251 - Do not pierce or burn, even after use.

Storage

P403 - Store in a well-ventilated place.

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Contains:

aqua, butane, isobutane, amyloextrin, propane, parfum, linalool, disodium tetraborate decahydrate, methylchloroisothiazolinone, methylisothiazolinone, borax decahydrate.

Ready-to-use product VOC content: 14.05%

UFI: 4W21-V0HE-R003-X8SD

2.3. Other hazards

It Contains :

disodium tetraborate decahydrate; borax decahydrate - SVHC

No information on other hazards

SECTION 3. Composition/information on ingredients**3.1 Substances**

Irrilevant

3.2 Mixtures

Refer to paragraph 16 for full text of hazard statements

Butane contains less than 0,1 % w/w 1,3-butadiene (EINECS No 203-450-8)

Note K - The harmonised classification as a carcinogen or mutagen applies unless it can be shown that the substance contains less than 0,1 % w/w 1,3- butadiene (Einecs No 203-450-8), in which case a classification in accordance with

Title II of this Regulation shall be performed also for those hazard classes. Where the substance is not classified as a carcinogen or mutagen, at least the precautionary statements (P102-)P210-P403 shall apply.

Substance	Concentration[w/w]	Classification	Index	CAS	EINECS	REACH
Butane Note: K	$\geq 5 < 15\%$	Flam. Gas 1A, H220 ATE inhal = 658,0mg/l/4 h	601-004-00-0	106-97-8	203-448-7	01-2119474 691-32
Isobutane	$\geq 1 < 5\%$	Flam. Gas 1A, H220 ATE oral = 570.000,0 mg/kg ATE dermal = 570.000,0 mg/kg ATE inhal = 658.000,0mg/l/4 h	601-004-00-0	75-28-5	200-857-2	01-2119485 395-27
Propane	$\geq 1 < 5\%$	Flam. Gas 1A, H220; Press. Gas, H280 ATE inhal = 410.000,0mg/l/4 h	601-003-00-5	74-98-6	200-827-9	01-2119486 944-21
disodium tetraborate decahydrate; borax decahydrate - SVHC	$\geq 0,10 < 0,30\%$	Repr. 1B, H360FD ATE oral = 2.660,0 mg/kg ATE dermal = 10.000,0 mg/kg	005-011-01-1	1303-96-4	215-540-4	ND

SECTION 4. First aid measures

4.1. Description of first aid measures

Inhalation:

Air the area. Move immediately the contaminated patient from the area and keep him at rest in a well ventilated area. If you feel unwell seek medical advice.

Direct contact with skin (of the pure product):

Wash thoroughly with soap and running water.

Direct contact with eyes (of the pure product):

Wash immediately and thoroughly with running water for at least 10 minutes.

Ingestion:

Not hazardous. It's possible to give activated charcoal in water or liquid paraffin medicine

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

If medical advice is needed, have product container or label at hand.

SECTION 5. Firefighting measures

5.1. Extinguishing media

Advised extinguishing agents:

CO2 or dry powder extinguisher

Extinguishing means to avoid:
Direct jets of water

5.2. Special hazards arising from the substance or mixture

The aerosol containers overheated burst and can be ejected with violence from a distance and can take place a dangerous mechanism for the fire.

Manufactured under pressure in sealed metal container (test pressure 15 bar max). Cool containers with water spray trying to remove them from the fire. The aerosol containers can be overheated and burst violently ejected from a distance (protect the head using a safety helmet).

5.3. Advice for firefighters

Use protection for the breathing apparatus
Safety helmet and full protective suit.

The spray water can be used to protect the people involved in the extinction

You may also use selfrespirator, especially when working in confined and poorly ventilated area and if you use halogenated extinguishers (Halon 1211 fluobrene, Solkan 123, NAF, etc...)

Keep containers cool with water spray

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel:

Leave the area surrounding the spill or release. Do not smoke

Leave the surrounding area recalling that any overheating could project the cylinder at a considerable distance.

Wear gloves and protective clothing

6.1.2 For emergency responders:

Wear protective gloves and clothing.

Eliminate all open flames and possible sources of ignition.

Not smoking.

Provide adequate ventilation.

Evacuate the danger area and, if necessary, consult an expert.

6.2. Environmental precautions

Contain spill

Inform the competent authorities.

Discharge the remains in compliance with the regulations

6.3. Methods and material for containment and cleaning up

6.3.1 For containment:

Recover the product for reuse, if possible, or the removal.

6.3.2 For cleaning up:

After wiping up, wash with water the area and materials involved

6.3.3 Other information:

None in particular.

6.4. Reference to other sections

Refer to paragraphs 8 and 13 for more information

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Avoid contact and inhalation of vapors

Use extreme caution when handling the product. Avoid shock or friction.

Do not smoke at work

At work do not eat or drink.

Vapors are heavier than air and may spread close to the ground and form explosive mixtures with air. Prevent formation of flammable or explosive concentrations in the air.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 ° C.

Do not pierce or burn, even after the use. Do not spray on flame or incandescent objects. Use in adequately ventilated areas.

See also paragraph 8 below.

7.2. Conditions for safe storage, including any incompatibilities

Keep in original container closed tightly. Do not store in open or unlabeled containers.

Keep containers upright and safe by avoiding the possibility of falls or collisions.

Pressurized container. Store in a ventilated place, in original packaging away from heat and sunlight.

Always store in well ventilated areas.

Never close the container tightly, leave a chance to vent

Keep away from open flames, sparks and heat sources. Avoid direct sunlight exposure.

7.3. Specific end use(s)

Industrial Manufacturing:

Handle with extreme caution.

Store in a well ventilated place away from heat sources.

Private households (= general public = consumers):

Handle with care.

Store in ventilated place away from heat sources,

Keep the container tightly closed.

Public domain (administration, education, entertainment, services, craftsmen):

Handle with care. Store in a ventilated area and away from heat, keep the container tightly closed.

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Related to contained substances:

Butane:

TLV (ACGIH) = 1000 ppm

ACGIH TLV (United States, 3/2012).

TWA: 1000 ppm 8 hour (s).

NIOSH REL (United States, 1/2013).

TWA: 1900 mg/m 10 hour (s).

TWA: 800 ppm 10 hour (s).

OSHA PEL 1989 (United States, 3/1989).

TWA: 1900 mg/m 8 hour (s).

TWA: 800 ppm 8 hour (s).

Butane EH40 WEL TWA 600 ppm 1.450 mg/m³

Isobutane:

ACGIH TLV (United States, 3/2012).

TWA: 1000 ppm 8 hour (s).

NIOSH REL (United States, 1/2013).
TWA: 1900 mg/m 10 hour (s).
TWA: 800 ppm 10 hour (s)

Propane:

TLV: (Aliphatic hydrocarbon gases) 1000 ppm as TWA; (ACGIH 2005).
ACGIH TLV (United States, 3/2012).
TWA: 1000 ppm 8 hour (s).
NIOSH REL (United States, 1/2013).
TWA: 1800 mg/m 10 hour (s).
TWA: 1000 ppm 10 hour (s).
OSHA PEL (United States, 6/2010).
TWA: 1800 mg/m 8 hour (s).
TWA: 1000 ppm 8 hour (s).
OSHA PEL 1989 (United States, 3/1989).
TWA: 1800 mg/m 8 hour (s).
TWA: 1000 ppm 8 hour (s)

8.2. Exposure controls

Appropriate engineering controls:

Industrial Manufacturing:

No specific monitoring foreseen

Private households (= general public = consumers):

No specific checks planned

Public domain (administration, education, entertainment, services, craftsmen):

No specific monitoring foreseen

Individual protection measures:

(a) Eye / face protection

Wear safety goggles to EN-166

(b) Skin protection

(i) Hand protection

Handle with gloves. Gloves must be checked before use. Use a technique suitable for removing gloves (without touching the outer surface of the glove) to avoid the skin contact with this product. Dispose of contaminated gloves after use in accordance with current legislation and good laboratory practices. Wash and dry your hands. The selected protective gloves have to satisfy the requirements of EU directive 89/686 / EEC and the resulting EN 374 standards.

Full contact

Material: Nitrile rubber

minimum thickness: 0.11 mm

breakthrough time: 480 min

The choice of an appropriate glove depends not only on the material but also on other quality characteristics which vary from one manufacturer to another.

For the choice of the type of gloves to use consult the supplier / manufacturer of the gloves.

Observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves.

(ii) Other

Avoid direct contact with the skin

Better is to use cotton antistatic clothing

(c) Respiratory protection

Work in a sufficiently ventilated to avoid inhaling the product.

(d) Thermal hazards

No hazard to report

Environmental exposure controls:

Use according to good working practices to avoid pollution into the environment.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical and chemical properties	Value	Determination method
Physical state	Aerosol	
Colour	irrelevant	
Odour	Characteristic	
Odour threshold	not determined	
Melting point/freezing point	not determined	
Boiling point or initial boiling point and boiling range	not determined	
Flammability	flammable	
Lower and upper explosion limit	8,5% (v/v) ; 1,5% (v/v)	
Flash point	< -10 °C	ASTM D92
Auto-ignition temperature	365 °C	
Decomposition temperature	not determined	
pH	irrelevant	
Kinematic viscosity	not determined	
Solubility	irrelevant	
Water solubility	irrelevant	
Partition coefficient n-octanol/water (log value)	not determined	
Vapour pressure	not determined	
Density and/or relative density	0,900 - 0,950 Kg/l	
Relative vapour density	not determined	
Particle characteristics	not determined	
Container volume	irrelevant	
Product volume	500 ml	
Pressure to 20°C	not determined	
Deformation pressure	not determined	
Burst pressure of the container	not determined	
Flash point of liquid phase	not determined	
Propellant flammability	flammable	

9.2. Other information

9.2.1 Information with regard to physical hazard classes

No data available.

9.2.2 Other safety characteristics

Content of VOC ready to use condition: 14,05 %

SECTION 10. Stability and reactivity

10.1. Reactivity

No reactivity hazards

10.2. Chemical stability

No hazardous reaction when handled and stored according to provisions.

10.3. Possibility of hazardous reactions

There are no hazardous reactions

10.4. Conditions to avoid

Avoid heating the product, it could explode.

Avoid contact with combustible materials. The product could catch fire.

heat, open flames, sparks or hot surfaces.

The aerosol product is stable for a period exceeding 36 months and in normal storage conditions can not take place dangerous reactions as the container is almost hermetically sealed.

To avoid that the metal container can deteriorate, keep away from acidic or basic products. Attention to the heat as temperatures exceeding 50 ° C has increased pressure inside the container that gets to deformation of the cylinder until the outbreak.

10.5. Incompatible materials

It can generate inflammable gases to contact with elementary metals, nitrides, strong reducing agents.

It can generate toxic gases to contact with oxidants mineral acids, organic peroxides, organic water peroxides.

It can ignite in contact with oxidants mineral acids, organic nitrides, peroxides and water peroxides, strong oxidants agents.

10.6. Hazardous decomposition products

Does not decompose when used for intended uses.

SECTION 11. Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

ATE(mix) oral = ∞

ATE(mix) dermal = ∞

ATE(mix) inhal = ∞

(a) acute toxicity: based on available data, the classification criteria are not met.

- (b) skin corrosion/irritation: based on available data, the classification criteria are not met.
(c) serious eye damage/irritation: based on available data, the classification criteria are not met.
(d) respiratory or skin sensitisation: based on available data, the classification criteria are not met.
(e) germ cell mutagenicity: based on available data, the classification criteria are not met.
(f) carcinogenicity: based on available data, the classification criteria are not met.
(g) reproductive toxicity: based on available data, the classification criteria are not met.
(h) specific target organ toxicity (STOT) single exposure: based on available data, the classification criteria are not met.
(i) specific target organ toxicity (STOT) repeated exposure based on available data, the classification criteria are not met.
(j) aspiration hazard: based on available data, the classification criteria are not met.

Related to contained substances:

Butane:

CL50 Inhalation (rat) vapour/dust/mist/fume (mg/l/4h) or gas (ppmV/4h) = 658

Isobutane:

LD50 (rat) Oral (mg/kg body weight) = 570000

LD50 Dermal (rat or rabbit) (mg/kg body weight) = 570000

CL50 Inhalation (rat) vapour/dust/mist/fume (mg/l/4h) or gas (ppmV/4h) = 658000

Propane:

CL50 Inhalation (rat) vapour/dust/mist/fume (mg/l/4h) or gas (ppmV/4h) = 410000

disodium tetraborate decahydrate; borax decahydrate:

Reproductive toxic

fetotoxicity

Alleged toxic for human reproduction

LD50 (rat) Oral (mg/kg body weight) = 2660

LD50 Dermal (rat or rabbit) (mg/kg body weight) = 10000

11.2. Information on other hazards

No data available.

SECTION 12. Ecological information

12.1. Toxicity

Related to contained substances:

Butane:

C(E)L50 (mg/l) = 7,71

Isobutane:

C(E)L50 (mg/l) = 7,71

Propane:

C(E)L50 (mg/l) = 7,71

disodium tetraborate decahydrate; borax decahydrate:

Toxic to fish LC50-*Carassius auratus* (goldfish)-178 mg/l-72 h

Toxic to daphnia and other aquatic invertebrates. -EC50 *Daphnia magna* (water Flea grande)-1,085-1,402 mg/l-48 h

Toxic for algae *Desmodesmus subspicatus* CI50-(green algae)-158 mg/l-96 h

C(E)L50 (mg/l) = 1,085

Use according to good working practices to avoid pollution into the environment.

12.2. Persistence and degradability

No data available.

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

Based on the available data, no PBT or vPvB substances are present in accordance with Regulation (EC) 1907/2006, annex XIII

12.6. Endocrine disrupting properties

No data available.

12.7. Other adverse effects

No adverse effects

SECTION 13. Disposal considerations

13.1. Waste treatment methods

The waste must be disposed of in compliance with the regulations in force delivering empty containers for final disposal and equipped to safely handle pressurized containers containing flammable liquids and gas waste. The empty container heated to temperatures exceeding 70 ° C can burst.

Recover if possible. Operate according to local or national regulations

SECTION 14. Transport information

14.1. UN number or ID number

ADR/RID/IMDG/ICAO-IATA: 1950

ADR exemption because compliance with the following characteristics:

Combination packagings: per inner packaging 1 L per package 30 Kg

Inner packagings placed in shrink-wrapped or stretch-wrapped trays: per inner packaging 1 L per package 20 Kg



14.2. UN proper shipping name

ADR/RID/IMDG: AEROSOL infiammabili

ADR/RID/IMDG: AEROSOL flammable

ICAO-IATA: AEROSOL flammable

14.3. Transport hazard class(es)

ADR/RID/IMDG/ICAO-IATA: Class : 2

ADR/RID/IMDG/ICAO-IATA: Label : 2.1 + Limited quantities

ADR: Tunnel restriction code : D
ADR/RID/IMDG/ICAO-IATA: Limited quantities : 1 L
IMDG - EmS : F-D, S-U

14.4. Packing group

ADR/RID/IMDG/ICAO-IATA: --

14.5. Environmental hazards

ADR/RID/ICAO-IATA: Product is not environmentally hazardous
IMDG: Marine polluting agent : Not

14.6. Special precautions for user

No data available.

14.7. Maritime transport in bulk according to IMO instruments

It is not intended to carry bulk

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso category:

P3a - FLAMMABLE AEROSOLS

REGULATION (EU) No 1357/2014 - waste:

HP3 - Flammable

Substances in the Candidate List (REACH Article 59)

disodium tetraborate decahydrate; borax decahydrate - SVHC

15.2. Chemical safety assessment

The supplier has made an assessment of chemical safety

SECTION 16. Other information

16.1. Other information

Points modified compared to previous release: 1.1. Product identifier, 1.2. Relevant identified uses of the substance or mixture and uses advised against, 2.2. Label elements, 2.3. Other hazards, 3.2 Mixtures, 6.1. Personal precautions, protective equipment and emergency procedures, 7.2. Conditions for safe storage, including any incompatibilities, 8.2. Exposure controls, 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008, 12.1. Toxicity, 12.5. Results of PBT and vPvB assessment, 12.6. Endocrine disrupting properties, 14.2. UN proper shipping name, 14.3. Transport hazard class(es), 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Description of the hazard statements exposed to point 3

H220 = Extremely flammable gas.

H280 = Contains gas under pressure; may explode if heated.

H360FD = May damage fertility. May damage the unborn child.

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008

[CLP]:

Classification according to Regulation (EC) Nr. 1272/2008

H223 - Flammable aerosol. Classification procedure: On basis of test data

H229 - Pressurised container: May burst if heated. Classification procedure: On basis of test data

Main normative references:

Directive 1999/45/EC

Directive 2001/60/EC

Regulation 1272/2008/EC

Regulation 2010/453/EC

** The information contained herein is based on our knowledge at the date above.

Related solely to the product and do not constitute a guarantee of a particular quality.

It is the duty of the user to ensure that these are appropriate and complete information regarding the specific use intended.

This data sheet cancels and replaces any previous edition.
